

# EXPLORER 8100

1.0m Stabilized, Auto-Acquire, Drive-Away Antenna System

February 2017 Product Sheet



## EXPLORER 8100 VSAT

A unique Dynamic Pointing Correction technology and an advanced carbon fiber reflector make the 1 meter EXPLORER 8100 the most advanced Auto-Acquire Drive-Away Land VSAT antenna available.

## Uninterrupted Communication

Traditional vehicle mounted 'Comms-On-The-Pause' VSAT antennas can lose connection to the satellite with even the slightest movement of the vehicle on its suspension caused by high winds or people getting in and out. EXPLORER 8100 isn't a traditional land VSAT antenna.

With EXPLORER 8100 you can enjoy continuous connectivity services even if the vehicle rocks thanks to a new and unique 'Dynamic Pointing Correction' system. Using lessons learned from Cobham SATCOM's maritime stabilized VSAT antennas, EXPLORER 8100 offers the most reliable connectivity available in its class.

## Reliable EXPLORER

EXPLORER 8100 is developed completely in-house by Cobham SATCOM. It features genuine EXPLORER design, which is already established and proven with Cobham SATCOM's highly regarded EXPLORER BGAN and GX terminals.

It is designed to offer unparalleled Comms-On-The-Pause performance, ensuring high-quality connectivity that is available even when other antennas would have lost their connection to the satellite. In the field, this means you can count on EXPLORER 8100 to provide you with vital communications whatever the conditions.

## Industry-Leading

EXPLORER 8100 features industry-leading fast satellite acquisition with pointing achieved typically in less than four minutes, making getting connected to a satellite a quick and easy process.

The system is available in both Ka- and Ku-band configurations and works with all major satellite networks. A swappable feed system allows users to change frequency bands, ensuring full choice of what services to use throughout the lifetime of the antenna.



## SYSTEM FEATURES

- Genuine EXPLORER Design
- Rugged, Reliable 1.0m Auto-Acquire Drive-Away Antenna
- Single Piece 1.0m Offset Feed Carbon Fiber Reflector for Multi-Band Ku/Ka Operation
- Built-in Wifi and a Web-based User Interface for easy PC and Smartphone Configuration
- Precision Polarization Drive in Ku-band configuration
- Dynamic Pointing Correction and inclined orbit satellite tracking
- Harmonic Drive Gear systems
- Advanced Blocking Zone Functionality
- Available in an 8W BUC, 20W BUC, and a no BUC option

*Subject to change without notice.*

[WWW.IPINTERNATIONAL.NET](http://WWW.IPINTERNATIONAL.NET)

# EXPLORER 8100

1.0m Stabilized, Auto-Acquire, Drive-Away Antenna System



ANTENNA CHARACTERISTICS	Ku-band		Ka-band (ViaSat eTRIA)	
	Receive	Transmit	Receive	Transmit
Frequency (GHz)	10.7 - 12.75	13.75 - 14.5	19.2 - 21.2	29.0 - 30.0
Antenna Gain	39.3 - 40.8	42.0 - 42.2	43.9 - 44.5	47.6 - 47.8
Cross Pol Isolation (dB) within 1dB beamwidth	>21.4	>25	>20.4	>20.5
Cross Pol Isolation (dB) On-Axis	>24.7	>32.2	-	-
Feed Port Isolation - Tx to Rx (dB)	40	110 w/filter	-	-
Beamwidth (degrees) at -3dB	1.6° - 1.9°	1.4° - 1.5°	1.1	0.7
Beamwidth (degrees) at -10dB	2.8° - 3.4°	2.5° - 2.6°	1.9	1.3
Antenna Noise Temp. (°K) at 30° Elevation	55°		107°	
G/T - Comm (dB/K)	18.4 dB/K @ 30° EL Midband		22.0 dB/K (eTRIA 1.5 dB Noise Figure)	
Radiation Pattern Compliance	FCC §25.209, ITU-R S.580		ITU-R S.580	
Polarization	Linear Orthogonal Std.		RHCP or LHCP (eTRIA auto selectable)	
Standard BUC Options	8 Watt / 20 Watt		3W ViaSat eTRIA	
EIRP with 8W / 20W BUC Options (dBW)	50 dBW / 54 dBW		54 dBW	

MECHANICAL	
Positioner	Harmonic Drive
Azimuth	± 195°
Elevation	0-100° antenna boresight (mechanical)
Polarization	± 95° (Ku-band)
Satellite Inclination	± 15°
Slewing & Deploying	Up to 9° per second
Acquisition time (typical)	<4 minutes from cold start

ELECTRICAL	
RF	Rx and Tx: Type F (75-ohm) connectors on ACU for modem interface
LNB (Ku)	Multi-band for international use included. (10.7 - 12.75 GHz)
Motors	Low noise, brushless, DC
Antenna Controller (1RU) Power Supply	90 - 264 VAC, 50/60Hz Single Phase 500W or 1000W option available. BUC Voltage Nom. 48VDC
ACU to antenna cable	10m cable harness, incl. Rx, Tx, BUC power and control, antenna power and control
Power Consumption	Motors Active – 290 Watts Motors Idle – 55 Watts

ENVIRONMENTAL	
Wind Speed: Operational (anchored)	72 km/h / 45 mph
Survival, deployed	118 km/h / 73 mph
Survival, stowed	161 km/h / 100 mph
Temperature: Operational	-33° to +55°C / -27° to 131°F
Survival	-40° to +80°C / -40° to 176°F
Rain	<100 mm/hr
Humidity	0 to 100% (condensing)

IP Rating: Antenna	IP-55
Antenna Control Unit	IP-30

REFLECTOR	
Size	1.0m single piece carbon fiber RTM reflector
Optics	Offset, Prime Focus
Mount Geometry	2-Axis, Elevation over Azimuth
Polarization	Ku-band: Linear with Motorized Rotation Ka-band: RHCP or LHCP

WEIGHT & MEASURES	
Weight	63 kg / 139 lbs with BUC / LNB 56.5 kg / 124.5 lbs with eTRIA
Length	156 cm / 61"
Stowed: Height / Width	35 cm / 14" / 100 cm / 39"
Antenna Control Unit (1RU)	
- Weight (500W / 1000W)	4.5 kg / 9.9 lbs. / 5.3 kg / 11.6 lbs.
- Dimensions	4.4 x 48 x 33 cm / 1.75" x 19" x 13"

PRODUCTS	
408157A-50211	EXPLORER 8100 Ku (8W BUC / 500W ACU)
408157A-50313	EXPLORER 8100 Ku (20W BUC / 1000W ACU)
408157A-50013	EXPLORER 8100 Ku (No BUC / 1000W ACU)
408157B-50551	EXPLORER 8100 Ka (ViaSat eTRIA)

ACCESSORIES	
408157A-100	EXPLORER 8100 Ku to KA-SAT Conversion Kit

For further information please contact:

IP Access International  
sales@ipinternational.net  
Tel: 949-655-1000

Subject to change without notice.